

CONSTRUCTING METHOD FOR SIMPLE FLOORING

Publication number: JP7229276 (A)

Publication date: 1995-08-29

Inventor(s): MATSUMOTO RIKA

Applicant(s): DANTANI PLYWOOD CO

Classification:

- **international:** *E04F15/00; E04F15/02; E04F15/04; E04F15/18; E04F15/00; E04F15/02; E04F15/04; E04F15/18;* (IPC1-7): E04F15/04; E04F15/00; E04F15/18

- **European:**


Application number: JP19940044911 19940219

Priority number(s): JP19940044911 19940219

Abstract of JP 7229276 (A)

PURPOSE:To obtain a simple floor-constructing method wherein construction is easy and even if flooring materials are used as flooring for floor heating, gaps are not likely appear between adjacent flooring materials because of heat.

CONSTITUTION:In a simple floor-constructing method wherein engagement grooves 16 each are formed at definite positions from joint end parts 13 on the undersides of adjacent flooring materials 10, a connector 17 is inserted into these grooves 16 and the adjacent flooring materials 10 are connected with each other, the connector 17 is composed of a flat bar-shaped connection plate part 18 and engaging plate parts 19 formed on both sides of the connection plate part 18, which parts 19 are bent on the same side. Furthermore, the top parts of the engaging plate parts 19 each are bent outside facing to each other.; At the central parts of the engaging plate parts, contact parts 21, 22, each of which elastically depresses the inner wall of the engagement groove 16, are formed protruding inside.



Data supplied from the **esp@cenet** database — Worldwide